

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**ACRYLIC CONFORMAL COATING**  
Bulk

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Anti Corrosion Products

**1.3. Details of the supplier of the safety data sheet**

CRC Industries UK Ltd.  
Wylds Road  
Castlefield Industrial Estate  
TA6 4DD Bridgwater Somerset  
United Kingdom  
Tel.: +44 1278 727200  
Fax.: +44 1278 425644  
E-mail : hse.uk@crcind.com

**1.4. Emergency telephone number**

(+44)(0)1278 72 7200 (office hours)



**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

<b>Physical:</b>	Flammable liquid, category 2 Highly flammable liquid and vapour.
Classification is based on test data.	
<b>Health:</b>	Eye irritation, category 2 Causes serious eye irritation. Specific target organ toxicity - single exposure, category 3 May cause drowsiness or dizziness.
Classification based on calculation method.	
<b>Environment:</b>	Not classified
Classification based on calculation method.	
<b>Other hazards :</b>	Repeated exposure may cause skin dryness or cracking.
<b>Other hazards :</b>	Not classified

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

<b>Product identifier:</b>	Contains: n-butyl acetate ethyl acetate
<b>Hazard pictogram(s):</b>	 
<b>Signal word:</b>	Danger
<b>Hazard statement(s):</b>	H225 : Highly flammable liquid and vapour. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.
<b>Precautionary statement(s):</b>	P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area. P280 : Wear protective gloves/protective clothing/eye protection/face protection. P403/233 : Store in a well-ventilated place. Keep container tightly closed. P501-2 : Dispose of contents/container to an authorised waste collection point.
<b>Supplemental Hazard information:</b>	Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

No information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
n-butyl acetate	01-2119485493-29	123-86-4	204-658-1	25-50	Flam. Liq. 3, STOT SE 3	H226,H336	
ethyl acetate	01-2119475103-46	141-78-6	205-500-4	25-50	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	B
<b>Explanation notes</b>							
B : substance with national established workplace exposure limit							
(* Explanation phrases : see chapter 16)							

## SECTION 4: First aid measures

### 4.1. Description of first aid measures



2 / 9

**CRC Industries UK Limited**  
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,  
Somerset, TA6 4DD  
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

<b>Contact with eyes :</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Contact with skin :</b>	Wash with water and soap. Seek medical attention if irritation persists
<b>Inhalation :</b>	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
<b>Ingestion :</b>	If swallowed do not induce vomiting Seek medical advice

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation :</b>	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting
<b>Skin contact :</b>	Mildly irritating to skin Symptoms : redness and pain
<b>Eye contact :</b>	Irritating to eyes Symptoms : redness and pain, impaired vision

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>General Advice :</b>	If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor
-------------------------	---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures  
Forms hazardous decomposition products  
CO,CO<sub>2</sub>

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing including eye/face protection.



**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

## 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

## 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

## 6.4. Reference to other sections

For further information see section 8

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/.../equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.  
Eyewash bottles should be available

## 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.  
Keep out of reach of children.

## 7.3. Specific end use(s)

Anti Corrosion Products

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

National established exposure limits, United Kingdom			
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm
National established exposure limits, Ireland			
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm

## 8.2. Exposure controls

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices.
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type A)
<b>hands and skin :</b>	Wear suitable protective gloves against chemicals. Check the appropriateness of the recommended gloves for your own particular conditions of use and replace gloves regularly after check for signs of damage or defects.
Recommended gloves:	(polyvinylalcohol)
<b>eyes :</b>	Wear safety eyewear according to EN 166.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance : physical state :</b>	Liquid.
<b>colour :</b>	Colorless.
<b>odour :</b>	Solvent.
<b>pH :</b>	Not applicable.
<b>Flash point :</b>	- 4 °C (Closed Cup)
<b>Relative density :</b>	0.93 (@ 20°C).
<b>Auto-ignition :</b>	> 200 °C

### 9.2. Other information

<b>VOC = volatile organic compounds</b>	745 g/l
---	---------

## SECTION 10: Stability and reactivity

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

**10.1. Reactivity**

No hazardous reactions known if used for its intended purpose

**10.2. Chemical stability**

Stable

**10.3. Possibility of hazardous reactions**

No hazardous reactions known if used for its intended purpose

**10.4. Conditions to avoid**

Avoid overheating

**10.5. Incompatible materials**

Strong oxidising agent

**10.6. Hazardous decomposition products**

CO,CO<sub>2</sub>

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

<b>acute toxicity:</b>	based on available data the classification criteria are not met
<b>skin corrosion/irritation:</b>	based on available data the classification criteria are not met
<b>serious eye damage/irritation:</b>	Causes serious eye irritation.
<b>respiratory or skin sensitisation:</b>	based on available data the classification criteria are not met
<b>germ cell mutagenicity:</b>	based on available data the classification criteria are not met
<b>carcinogenicity:</b>	based on available data the classification criteria are not met
<b>toxicity for reproduction:</b>	based on available data the classification criteria are not met
<b>STOT-single exposure:</b>	May cause drowsiness or dizziness.
<b>STOT repeated exposure:</b>	based on available data the classification criteria are not met
<b>aspiration hazard:</b>	based on available data the classification criteria are not met

**Information on likely routes of exposure:**

<b>Inhalation :</b>	Excessive inhalation of vapours may give rise to irritation and affect the nervous system
<b>Skin contact :</b>	Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
<b>Eye contact :</b>	Irritating to eyes

**Toxicological data :**

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

Hazardous ingredient	CAS-nr.	method	
n-butyl acetate	123-86-4	LD50 oral rat	10760 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 1400 mg/kg
ethyl acetate	141-78-6	LD50 oral rat	5620 mg/kg
		LC50 inhal.rat	30 mg/l
		LD50 derm.rabit	> 20000 mg/kg

## SECTION 12: Ecological information

### 12.1. Toxicity

Not classified

#### Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
n-butyl acetate	123-86-4	IC50 algae	647 mg/l
		LC50 fish	18 mg/l
		EC50 daphnia	44 mg/l
ethyl acetate	141-78-6	IC50 algae	5600 mg/l
		LC50 fish	230 mg/l
		EC50 daphnia	610 mg/l

### 12.2. Persistence and degradability

No experimental data available

### 12.3. Bioaccumulative potential

No experimental data available

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No experimental data available

## SECTION 13: Disposal considerations



7 / 9

**CRC Industries UK Limited**  
Ambersil House, Wylds Road, Castlefield Industrial Estate, Bridgwater,  
Somerset, TA6 4DD  
Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.ambersil.com

**Productname :** ACRYLIC CONFORMAL COATING **Creationdate :** 14.10.20 Version : 3.2  
**Ref.Nr.:** BDS000941\_3\_20201014 (EN) **Replaces:** BDS000941\_20200624

**13.1. Waste treatment methods**

Do not discharge into drains or the environment, dispose to an authorised waste collection point.

**National regulations :** Disposal should be in accordance with local, state or national legislation

**SECTION 14: Transport information****14.1. UN number**

UN-number : 1263

**14.2. UN proper shipping name**

Proper shipping name: PAINT

**14.3. Transport hazard class(es)**

Class: 3  
ADR/RID - Classification code: F1

**14.4. Packing group**

Packing group: II

**14.5. Environmental hazards**

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

**14.6. Special precautions for user**

ADR/RID - Tunnelcode: (D/E)  
IMDG - Ems: F-E, S-E  
IATA/ICAO - PAX: 353  
IATA/ICAO - CAO: 364

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**



<b>Productname :</b>	ACRYLIC CONFORMAL COATING	<b>Creationdate :</b>	14.10.20 Version : 3.2
<b>Ref.Nr.:</b>	BDS000941_3_20201014 (EN)	<b>Replaces:</b>	BDS000941_20200624

The Safety Data Sheet is compiled according to the current European requirements.  
Regulation (EC) No 1907/2006 (REACH)  
Regulation (EC) No 1272/2008 (CLP)

## 15.2. Chemical safety assessment

No information available

## SECTION 16: Other information

\*Explanation hazard statements: H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.

acronyms and synonyms: TWA = time weight average  
STEL = short time exposure limit  
VOC = volatile organic compounds  
PBT = persistent bioaccumulative toxic  
vPvB = very persistent very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.